

Standard Silicon Rectifiers

Reverse Voltage - 1000 V

Forward Current - 20 A

FEATURES

- ◆ Low cost . Diffused junction
- ◆ Low Leakage
- ◆ Low forward voltage drop
- ◆ High current capability
- ◆ Easily cleaned with Freon. Alcohol. Isopropanol and similar solvents
- ◆ Lead free in comply with EU RoHS 2011/65/EU directives


MECHANICAL DATA

- ◆ Case: R-6
- ◆ Terminals: Solderable per MIL-STD-750, Method 2026
- ◆ Approx. Weight: 2.05g / 0.072oz

Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.



Parameter	Symbols	20A10	Units
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	1000	V
Maximum RMS voltage	V_{RMS}	700	V
Maximum DC Blocking Voltage	V_{DC}	1000	V
Maximum Average Forward Rectified Current 9.5mm Lead Length. at $T_A = 75^{\circ}C$	$I_{F(AV)}$	20.0	A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load $T_j = 125^{\circ}C$	I_{FSM}	800	A
Maximum Instantaneous Forward Voltage at 20A	V_F	1.0	V
Maximum DC Reverse Current $T_a = 25^{\circ}C$ at Rated DC Blocking Voltage $T_a = 100^{\circ}C$	I_R	10.0 100	μA
Typical Junction Capacitance	C_j	200	pF
Typical Thermal Resistance	$R_{\theta JA}$	10	$^{\circ}C/W$
Operating and Storage Temperature Range	T_j, T_{stg}	-50 ~ +125	$^{\circ}C$

Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic





Fig.6 Maximum Non-Repetitive Peak Forward Surge Current



Ordering information

Package	Packing Description	Packing Quantity
R-6	ammo pack	500PCS/Inner Box 5000PCS/Carton

Package Dimensions

R-6

Dim.	Millimeter(mm)		INCHES	
	Min.	Max.	Min.	Max.
A	8.60	9.10	0.340	0.360
B	8.60	9.10	0.340	0.360
C	1.20	1.30	0.048	0.052
D	25.40	-	1.00	-

Disclaimer

The information presented in this document is for reference only. Guangdong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.