


30V N-CHANNEL ENHANCEMENT MODE MOSFET

MAIN CHARACTERISTICS

I_D	4.2A
V_{DSS}	30V
R_{DS(on)-typ(@V_{GS}=10V)}	<42mΩ(Typ:32 mΩ)



Marking Code	
YFW3400C	A09T

Application

- ◆ Battery protection
- ◆ Load switch
- ◆ Uninterruptible power supply

Maximum Ratings at T_c=25°C unless otherwise specified

Characteristics	Symbols	Value	Units
	V_{DS}	30	V
Gate - Source Voltage	V_{GS}	±12	V
Continuous Drain Current T _A =25°C	I_D	4.2	A
Continuous Drain Current T _A =100°C	I_D	2.6	A
Pulsed Drain Current	I_{DM}	16	A
Power Dissipation T _A = 25°C	P_D	1.1	W
Thermal Resistance, Junction to Case	R_{θJA}	113.6	°C/W
Operating Junction Temperature Range	T_J, T_{STG}	-55 to +150	°C







Maximum Ratings at Tc=25°C unless otherwise specified

Characteristics	Test Condition	Symbols	Min	Typ	Max	Units
Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	V(BR)DSS	30	32	-	V
Zero Gate Voltage Drain Current	$V_{DS}=30V, V_{GS}=0V$	I_{DSS}	-	-	1.0	μA
Gate to Body Leakage Current	$V_{GS}=\pm 12V, V_{DS}=0V$	I_{GSS}	-	-	±100	nA
Gate -Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	V_{GS(th)}	0.5	0.9	1.4	V
Static Drain-Source on-Resistance note2	$V_{GS}=10V, I_D=4A$	R_{DS(ON)}	-	32	42	mΩ
	$V_{GS}=4.5V, I_D=3A$		-	36	48	
	$V_{GS}=2.5V, I_D=2A$		-	50	70	
Input Capacitance	$V_{DS}=15V$ $V_{GS}=0V$ $f=1.0MHz$	C_{iss}	-	285	-	pF
Output Capacitance		C_{oss}	-	33	-	
Reverse Transfer Capacitance		C_{rss}	-	27	-	
Total Gate Charge	$V_{DS}=15V$ $V_{GS}=4.5V$ $I_D=4A$	Q_g	-	2.6	-	nC
Gate-Source Charge		Q_{gs}	-	0.6	-	
Gate-Drain("Miller") Charge		Q_{gd}	-	0.9	-	
Turn-on delay time	$V_{DS}=15V, I_D=2A,$ $R_{GEN}=3\Omega, V_{GS}=4.5V$	t_{d(on)}	-	15	-	ns
Turn-on Rise Time		T_r	-	42	-	
Turn-Off Delay Time		t_{d(OFF)}	-	16	-	
Turn-Off Fall Time		t_f	-	10	-	
Maximum Continuous Drain to Source Diode Forward Current		I_S	-	-	4	A
Maximum Pulsed Drain to Source Diode Forward Current		I_{SM}	-	-	16	A
Drain to Source Diode Forward Voltage	$V_{GS}=0V, I_S=4A$	V_{SD}	-	-	1.2	V

Note :

- 1、 The data tested by surface mounted on a 1 inch2 FR-4 board with 2OZ copper.
- 2、 The data tested by pulsed , pulse width $\cong 300\mu s$, duty cycle $\cong 2\%$
- 3、 The power dissipation is limited by 150°C junction temperature
- 4、 The data is theoretically the same as ID and IDM , in real applications , should be limited by total power dissipation.

Typical characteristics



Ordering information


Package	Packing Description	Base Quantity	Packing Quantity
SOT-23	Tape/Reel,7"reel	3000pcs/Reel	24000PCS/Box 120000PCS/Carton

Package Dimensions

SOT-23

Dim.	Millimeter (mm)		mil	
	Min.	Max.	Min.	Max.
A	0.9	1.15	35	45
A1	0.1		3.9	
bp	0.38	0.48	15	19
C	0.09	0.15	3.54	5.9
D	2.8	3.0	110	118
E	1.2	1.4	47	55
E	1.9		75	
E1	0.95		37	
HE	2.1	2.55	83	100
Lp	0.15	0.45	5.9	18
Q	0.45	0.55	18	22
v	0.2		7.9	
W	0.1		4	

The recommended mounting pad size



Disclaimer

The information presented in this document is for reference only. Guangdong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.