


NPN Transistors

Features

- Ideal for Medium Power Amplification and Switching
- Complementary PNP Type Available (MMBT4403)

Marking Code	
MMBT4401	2X



Absolute Maximum Ratings (Ta=25°C)









Parameter	Symbol	Rating	Unit
Collector-base voltage	V _{CB0}	60	V
Collector-emitter voltage	V _{CEO}	40	V
Emitter-base voltage	V _{EBO}	6.0	V
Collector current	I _C	600	mA
Total Device Dissipation Alumina Substrate	P _D	300	mW
Thermal Resistance, Junction to Ambient	R _{θJA}	417	°C/W
Junction and Storage Temperature	T _J , T _{stg}	-55 to 150	°C

Electrical Characteristics (Ta=25°C unless otherwise specified.)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	V _{(BR)CBO}	I _C = 100μA, I _E = 0	60			V
Collector-emitter breakdown voltage	V _{(BR)CEO}	I _C = 1.0 mA, I _B = 0	40			V
Emitter-base breakdown voltage	V _{(BR)EBO}	I _E = 100μA, I _C = 0	6.0			V
Collector cut-off current	I _{CBO}	V _{CB} = 50 V, I _E = 0			0.1	μA
Emitter cut-off current	I _{EBO}	V _{EB} = 5V, I _C = 0			0.1	μA
DC current gain *	h _{FE}	I _C = 0.1 mA, V _{CE} = 1.0 V	20			
		I _C = 1.0 mA, V _{CE} = 1.0 V	40			
		I _C = 10 mA, V _{CE} = 1.0 V	80			
		I _C = 150 mA, V _{CE} = 1.0 V	100		300	
		I _C = 500 mA, V _{CE} = 2.0 V	40			
Collector-emitter saturation voltage *	V _{CE(sat)}	I _C = 150 mA, I _B = 15 mA			0.4	V
		I _C = 500 mA, I _B = 50 mA			0.75	
Base-emitter saturation voltage *	V _{BE(sat)}	I _C = 150 mA, I _B = 15 mA	0.75		0.95	V
		I _C = 500 mA, I _B = 50 mA			1.2	
Transition frequency	f _T	I _C = 20 mA, V _{CE} = 10 V, f = 100 MHz	250			MHz
Delay time	t _d	V _{CC} = 30 V, V _{EB} = 2.0 V,			15	ns
Rise time	t _r	I _C = 150 mA, I _{B1} = 15 mA			20	ns
Storage time	t _s	V _{CC} = 30 V, I _C = 150 mA,			225	ns
Fall time	t _f	I _{B1} = I _{B2} = 15 mA			30	ns

* Pulse test: pulse width ≤ 300 μs, duty cycle ≤ 2.0%.

Typical Characteristics



Ordering information


Package	Packing Description	Base Quantity	Packing Quantity
SOT-23	Tape/Reel,7"reel	3000pcs/Reel	24000PCS/Box 120000PCS/Carton

Package Dimensions

SOT-23

Dim.	Millimeter (mm)		mil	
	Min.	Max.	Min.	Max.
A	0.9	1.15	35	45
A1	0.1		3.9	
bp	0.38	0.48	15	19
C	0.09	0.15	3.54	5.9
D	2.8	3.0	110	118
E	1.2	1.4	47	55
E	1.9		75	
E1	0.95		37	
HE	2.1	2.55	83	100
Lp	0.15	0.45	5.9	18
Q	0.45	0.55	18	22
v	0.2		7.9	
W	0.1		4	

The recommended mounting pad size



Disclaimer

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.